

PURA
Niedervolt Pendelleuchten

Low-Voltage Pendant Lights

PURA nennen wir die Pendelleuchterserie mit dem ganz besonderen Schimmer, auf dieser und den nächsten Seiten.

Modernes Handwerk und aktuelle Technik im Umgang mit traditionsreichem Material lassen Leuchten einer sehr eigenen Transparenz und Zartheit entstehen.

Unglasiert, mit den vom Werkstoff Porzellan vorgegebenen Ungenauigkeiten und dem strukturveränderten Design ist jedes Stück ein Unikat.

Wie alle unsere Porzellanleuchten werden die Schirme in Handarbeit in einem aufwändigen Fertigungsverfahren in der Porzellanmanufaktur hering BERLIN hergestellt. Alle Leuchten sind mit einem 2000 oder 3000 mm langen Koaxkabel und STENG Steckverbindern ausgestattet. Um die Lichtwirkung nach unten zu erhöhen empfehlen wir das neue OSRAM Leuchtmittel „Ministar“, Seite 218.

Montageteile siehe Kapitel Basiselemente.

PURA is the name of a pendant light line with a very special glow. Modern technology, traditional materials and skilled craftsmanship unite to create lights with a gentle, shimmering translucence. Each light is unique, with the natural irregularities of porcelain used to great effect by an unglazed finish, and a design which is perfectly matched to the material's texture. Made by the porcelain manufacture hering BERLIN. The best light effect can be achieved with the new OSRAM "Ministar" bi-pin lamps. Depending on the product, a variety of patterns is available. The lights are fitted with a 2000mm/79" or 3000mm / 118" coaxial cable. For use with bi-pin lamps. To mount the low-voltage lamp, one of the basic elements from page 150-190 is required.

hering
 by
 STENG
 LICHT

Design: Stefanie Hering, Peter Steng

PYRAMID PURA

PPY 



POD



PQU



PLÄ



CORNET PURA

PCO 




POD



PQU



PLÄ



CLIVA PURA

PCL 




POD







PHQ



PQU



Leuchtmittel / Lamps

	QTL P 9 QTL P 12	12 V max 35 W	G4 GY 6,35
	QR-C 16	12 V max 35 W	GU 4 GY 6,35
IP 40			Mini Star

Kabellänge / Cable length

- 2 0** 2000mm / 79"
- 3 0** 3000mm / 118"

(Letzte Art. Nr. / Final article codes)

